
INTERGRATED AV AMPLIFIER


KA-894/994/V3700 SERVICE MANUAL

KENWOOD

©1994-1 PRINTED IN KOREA B51-4846-00(K)3576

(KA-994)





KA-894/994/V3700

CONTENTS

CCESSORIES 2 EMOTE CONTROL 4 OCK DIAGRAM 6 RCUIT DESCRIPTION 7 DJUSTMENT 13 IRING DIAGRAM 14	PC BOARD
ACCESSORIES	
• Remote control unit1 (A70-0974-05) 'KA-894/V3700	(A70-0961-05) KA-994
Battery cover (A09-0170-08)	Battery cover (A09-0169-08)
RC-S0800	RC-R0801
• AC plug adaptor1 (E03-0115-05) KA-994, 894(M)	• Batteries(R6/AA)2 (—)

(KA-894 / V3700)






Photo is KA-V3700.

(KA-894)



(KA-V3700)




REMOTE CONTROL

REMOTE CONTROL ASSY: A70-0961-05 (KA-994)

Operating the KR-V8060 or KA-994


- Press the AUDIO key to display "AUDIO".
- 2 Press the **POWER** key to turn the power of the main unit (KR-V8060 or KA-994) ON
- 3 Press operation keys.


 The keys covered with are not used in the operation of the receiver.



Model: RC-R0801 Infrared ray system

REMOTE CONTROL ASSY: A70-0974-05 (KA-894/V3700)





BLOCK DIAGRAM

TEST MODE

1 To get in the TEST MODE

Plug the AC power cord in the wall outlet while pushing the SPEAKERS key.

All indications light up.

(2) To cancel the TEST MODE

Unplug the AC power cord from the wall outlet.

③ Operation during the TEST MODE

- <1> The TEST MODE starts with all indications lit up and with POWER ON.
 - The Light up state returns to the normal operation state when any key of the main unit is pushed.
- <2> Keys that have different functions from their normal functions in the test mode

BALANCE L Three steps change from R to Center to L.

BALANCE R Three steps change from L to Center to R.

DELAY TIME + Three steps change from Minimum to Center to Maximum.

DELAY TIME – Three steps change from Maximum to Center to

CENTER LEVEL + Three steps change from Minimum to Center to Maximum.

CENTER LEVEL — Three steps change from Maximum to Center to Minimum.

REAR LEVEL + Three steps change from Minimum to Center to

Maximum.

REAR LEVEL — Three steps change from Maximum to Center to Minimum.

 $8\Omega/4\Omega$ Switch Switch status is indicated by TAPE 2 display.

 8Ω : TAPE 2 display goes off. 4Ω : TAPE 2 display lights up.

At any time TAPE 2 display is indicated,

however H/L

switch of 70W/100W control port (pin no.9) is

switched when. . .

Power ON or OFF

SPEAKER ON or OFF

DOLBY Mode or BYPASS

Switching with INPUT SELECTOR

INITIAL SETTING

1 Initial setting

Plug the AC power cord in the wall outlet while pushing the SPEAKERS key.

- ♦ All memorys are cleared.
- The backup operation is returned to the normal operation.

SERIAL TEST MODE

1 To get in the SERIAL TEST MODE

Enter the TEST ON code (71).

② To cancel the SERIAL TEST MODE

Enter the TEST OFF code (70), unplug the AC power cord from the electrical outlet, or RESET the equipment.

♦ The operation returns from the test mode to the normal mode.

③ Operation during the SERIAL TEST MODE

- The following functions become ineffective during the test mode.
 - ♦ Keys of the main unit, keys of the remote controller, ordinary serial codes.

The same codes as the received ones are outputted.

- Output of the MUTE signal.
 - The MUTE function does not work during the SERIAL TEST MODE. The operation of the MUTE function is checked with a specific code.
- Codes received during the SERIAL TEST MODE are effective irrespective of the display mode.
- The key entry inhibit state with 16-second duration is not available when the ADAPTOR is turned ON/OFF.
- When the initial setting is carried out by means of the initial setting AMP (3F) and the initial letting GE (DF) code.
 - SPEAKERS A/B turn OFF in response toso ftware operation.

<u> </u>																	
	<u>u</u>																
	ш															0	()
	Q														LIGHT UP	LIGHT UP OFF	SETTING (GE)
GE	O	POWER OFF	POWER	MUTE OFF	MUTE	P.F.	O S	M1 (ALL MID)	M2 (ALL MAX)	M3 (ALL MIN)				·			
	æ	ACOUSTIC II BGM		CINEMA SCREEN 1	CINEMA SCREEN 2	CINEMA SCREEN 3	CH.MODE	CH.MODE	CH.MODE 4	CH.MODE 5							SETTING (SURROUND)
QND	4	ASFC /		SEAT POS MID	SEAT POS MAX	WALL	WALL	WALL	ROOM SIZE MIN	ROOM SIZE MID	ROOM SIZE MAX	STEREO (KARAOKE)	MULTI (KARAOKE)	HIFI MULTI (KARAOKE)		ACOUSTIC NON DIRE 1	ACOUSTIC NON DIRE 2
SURROUND	6	REAR MUTE ON	MUTE ALL OFF	CENTER LEVEL MIN	CENTER LEVEL MID	CENTER LEVEL MAX	REAR LEVEL MIN	REAR LEVEL MID	REAR LEVEL MAX	DILAY TIME MIN	DILAY TIME MID	DILAY TIME MAX	PRESENCE LEVE (EFECT)MIN	PRESENCE LEVE (EFECT)MID	PRESENCE LEVE (EFECT)MAX	ASFC	ASFC
	8	POWER	POWER	BYPASS	DOLBY SUR- ROUND	DOLBY 3 STEREO	dSO	DSP	S.4CH	F.4CH	CENTER MODE NORMAL	CENTER MODE WIDE	CENTER MODE PHANTOM	TEST OFF	TEST TONE ON	FRONT MUTE ON	CENTER MUTE ON
	7	TEST OFF	TEST														
EB	9	MEMORY	MAIN	SUB	ВОТН												
TUNER	45	0	-	2	6	4	5	9	7	80	6	+10	BAND FM	BAND AM/MW	BAND TV/LW	DOWN	В
	4	POWER	POWER	MUTE	MUTE	AUTO STEREO	MONO	TUNED	TUNED	A.R OFF	A.R ON	RF DIRECT	RF DISTANCE	IF WIDE	IF NORMAL	IF NARROW	DIRECT
	· ·														ALL LIGHT UP ON	ALL LIGHT UP OFF	SETTING (AMP)
	6	SP B OFF	SP B NO	MASTER	HIT MASTER ON	MOTOR VOL UP	MOTOR VOL DOWN	MOTOR VOL STOP	DBS/TV	VR 0dB	-20dB	-30dB	-70dB	8	BALANCE L	BALANCE	BALANGE
AMP	-	DIRECT	DIRECT PRECT	1	CD REC	SOURCE DIRECT OFF		뇄		LOUD- NESS OFF	LOUD- NESS ON	SUB SONIC OFF	SUB SONIC ON	S WOOFER OFF	S WOOFER ON	SP OFF (SP A OFF)	SP ON (SP A ON)
		E L		PHONO	a _S	TUNER	TAPE 1 (TAPE A)	TAPE 2 (TAPE B)	AUX	DAT	VIDEO 1 (VIDEO)	VIDEO 2	VIDEO 3	VDP	MUTE	SELMUTE	MUTE ALL OFF
TYPE	/ ₽	0	-	2	က	4	5	9	7	80	6	A	В	ပ	Q	w	IJ.

8 bit SERIAL TEST CODE

KEY MATRIX


	KRO	KRI	KR2		
FL. A. p/KS00		CENTER SPEAKER VOLUME DOWN	Dolby 3-Stereo	S20	54pin
FL. A. n/KS01	CENTER MODE	CENTER SPEAKER VOLUME UP	Dolby Pro Logic	S19	53pin
FL. A. m/KS02	BALANCE R	REAR SPEAKER VOLUME DOWN	BYPASS	S18	52pin
FL. A. k/KS03	BALANCE L	REAR SPEAKER VOLUME UP	LOUDNESS	S17	51pin
FL. A. j/KS04	TEST-TONE	DELAY TIME DOWN	LINE- STRAIGHT	S16	50pin
FL. A. a/KS05	SPEAKER ON/OFF	DELAY TIME UP	POWER	PF7/S15	49PI N
FL. A. b/T. o/KS06				PF6/S14	48PI N
FL. A. h/T. n/KS07				PF5/S13	47PIN
FL. A. f/T. m/KS08				PF4/S12	46PIN
FL. A. g/T. I/KS09				PF3/S11	45PI N
FL. A. d/T. k/KS10				PF2/S10	44PI N
FL. A. c/T. j/KS11				PF1/S09	43PI N
FL. A. e/T. i/KS _{INI} 1				PF0/S08	42PI N
FL. T. h/KS _{INI} 2	DSW3	DSW4	DSW5	PD7/S07	41PIN
•	PC0/KR0	PC1/KR1	PC2/KR2		
	14nin	15pin	16pin		

	DSW3	DSW4	DSW5
KA-894	NO.	NO	NO
KA-994	NO	YES	YES
KA-V3700	NO	YES	YES

KA-894/994/V3700

CIRCUIT DESCRIPTION

PIN LAYOUT
MICRO PROCESSOR CXP82320-158Q <BOTTOM VIEW>



Pin description

Pin No.	Pin Name	I/O	Name	Description
1	PE3/INT3		VOL. CCW	Input of ROTARY ENCODER PHASE B signal for VOLUME
2	PE4/RMC	I	REMOCON	REMOTE CONTROLLER signal input
3	PE5		PROTECT	PROTECTION control signal input
4	PE6	0	VOL1/2. DT	Output of DATA signal for control of electronic VOLUME (TC9212P/TC9213P)
5	PE7/T0	0	VOL1/2. CK	Output of CLOCK signal for control of electronic VOLUME (TC9212P/TC9213P
6	PB0/CINT	0	VOL1. ST	Output of STROBE signal for control of electronic VOLUME (TC9212P/TC9213
7	PB1/CS0	0	VOL2. ST	Output of STROBE signal for control of electronic VOLUME (TC9213P)
8	PB2/SCK0	0	MUTE	MUTING circuit control signal output L:ON, H:OFF
9	PB3/SI0	0	100W/70W	100W/70W RELAY control signal output L:70W, H:100W
10	PB4/SO0	0	SEL. CK	Output CLOCK signal for control of SELECTOR (TC9164N)
11	PB5/SCKI	0	SEL. ST	Output STROBE signal for control of SELECTOR (TC9164N)
12	PB6/SI1	0	SEL. DT	Output DATA signal for control of SELECTOR (TC9164N)
13	PB7/SO1	0	DOLBY, ST	Output of ENABLE signal for control of DOLBY IC (LA2785/LV1010)
14	PC0/KR0	1	KR0	KEY RETURN signal input
15	PC1/KR1	1	KR1	KEY RETURN signal input
16	PC2/KR2	Ī	KR2	KEY RETURN signal input
17	PC3/KR3	0	DOLBY, DT	Output of DATA signal for control of DOLBY IC (LA2785/LV1010)
18	PC4/KR4	0	DOLBY, CK	Output of CLOCK signal for control of DOLBY IC (LA2785/LV1010)
19	PC5/KR5	0	HP. RELAY	HEADPHONE RELAY control signal output (LC7218)
20	PC6/KR6	0	4Ω / 8Ω	Speaker impedance switching (LC7218)
21	PC7/KR7	0	SEL2. A	LINE STRAIGHT control signal output (TC9215P)
22	PA0/AN0	0	VIDEO. A	VIDEO SELECTOR A control signal output (NJM2279D)
23	PA1/AN1	0	VIDEO, B	VIDEO SELECTOR B control signal output (NJM2279D)
24	PA2/AN2	0	SEL1. A	LINE STRAIGHT control signal output (TC9215P)
25	PA3/AN3	0	SEL1. B	PHONO select signal output (TC9215P)
26	PA4/AN4	0	SEL1. C	CD/TUNER select signal output (TC9215P)
27	PA5/AN5	1/0	SERIAL. BUSY	System serial BUSY signal input/output
28	PA6/AN6	1/0	SERIAL. DATA	System serial DATA signal input/output
29	PA7/AN7	I	CE	BACK UP detection
30	RST	1/0	RESET	RESET signal detection
31	EXTAL	I		System Clock input (10MHz)
32	XTAL			System Clock (10MHz)
33	Vss			GND
34	PD0/S0	0	T.a	Unused
35	PD1/S1	0	T.b	Unused
36	PD2/S2	0	T.c	Unused
37	PD3/S3	0	T.d	Unused
38	PD4/S4	0	T.e	Unused
39	PD5/S5	0	T.f	Unused
40	PD6/S6	0	T.g	Unused

KA-894/994/V3700

CIRCUIT DESCRIPTION


Pin description


Pin No.	Pin Name	1/0	Name	Description
41	PD7/S7	0	KS13	KEY SCAN 13 signal output
42	PF0/S8	0	A.e	FL tube segment e(pin no.35) driving signal output
43	PF1/S9	0	A.c	FL tube segment c(pin no.34) driving signal output
44	PF2/S10	0	A.d	FL tube segment d(pin no.33) driving signal output
45	PF3/S11	0	A.g	FL tube segment g(pin no.32) driving signal output
46	PF4/S12	0	A.f	FL tube segment f(pin no.31) driving signal output
47	PF5/S13	0	A.h	FL tube segment h(pin no.30) driving signal output
48	PF6/S14	0	A.b	FL tube segment b(pin no.29) driving signal output
49	PF7/S15	0	KS5/A.a	KEY SCAN 5 signal output FL tube segment a(pin no.28) driving signal output
50	S16	0	KS4/A.j	KEY SCAN 4 signal output FL tube segment (pin no.27) driving signal output
51	S17	0	KS3/A.k	KEY SCAN 3 signal output FL tube segment k(pin no.26) driving signal output
52	S18	0	KS2/A.m	KEY SCAN 2 signal output FL tube segment m(pin no.25) driving signal output
53	S19	0	KS1/A.n	KEY SCAN 1 signal output FL tube segment n(pin no.24) driving signal output
54	S20	0	KS0/A.p	KEY SCAN 0 signal output FL tube segment p(pin no.23) driving signal output
55	T15/S21	0	A.r	FL tube segment r(pin no.22) driving signal output
56	T14/S22	0	A.s	FL tube segment s(pin no.21) driving signal output
57	T13/S23	0	A.t	FL tube segment t(pin no.20) driving signal output
58	T12/S24	0		Unused
59	T11/S25	0		Unused
60	T10/S26	0	A.11G	FL tube segment 11G(pin no.15) driving signal output
61	T9/S27	0	A.10G	FL tube segment 10G(pin no.14) driving signal output
62	T8/S28	0	A.9G	FL tube segment 9G(pin no.13) driving signal output
63.	77	0	A.8G	FL tube segment 8G(pin no.12) driving signal output
64	T6	0	A.7G	FL tube segment 7G(pin no.11) driving signal output
65	T5	0	A.6G	FL tube segment 6G(pin no.10) driving signal output
66	T4	0	A.5G	FL tube segment 5G(pin no.9) driving signal output
67	T3	0	A.4G	FL tube segment 4G(pin no.8) driving signal output
68	T2	0	A.3G	FL tube segment 3G(pin no.7) driving signal output
69	T1	0	A.2G	FL tube segment 2G(pin no.6) driving signal output
70	TO	0	A.1G	FL tube segment 1G(pin no.5) driving signal output
70	Vfdp			FL pre-driver POWER SUPPLY (-30V)
	Vdd			Microprocessor POWER input (+5V)
72	NC NC		NC	Unused pull up (+15V)
73	PG0	0	LED	STAND BY LED drive output
74	PG1	0	POWER	POWER RELAY control signal output
75	PG2	0	F. RELAY	FRONT RELAY control signal output
76	PG3	0	C/S. RELAY	CENTER/SURROUND control signal output
77	PEO/ECO/INTO	1.	SEL. CW	Input of BOTARY ENCODER PHASE A signal output for INPUT SELECTOR
78		1.	SEL. CCW	Input of ROTARY ENCODER PHASE B signal output for INPUT SELECTOR
79	PE1/EC1/INT1 PE2/IN2		VOL. CW	Input of ROTARY ENCODER PHASE A signal output for VOLUME

ADJUSTMENT

ADJUSTMENT

No.	ITEM	INPUT SETTINGS	OUTPUT SETTINGS	AMPLIFIER SETTING	ALIGNMENT POINTS	ALIGN FOR	FiG
	Unless otherwise speci POWER : ON SELECT		ive switches as follows: AL) SURROUND : PRO LC	ogic			· · · · · · · · · · · · · · · · · · ·
1	IDLE CURRENT		Connect a DC voltmeter across CP1 (L) CP2 (R)	VOLUME: 0	VR1 (L) VR2 (R) (X09-)	13.2mV	(a)
			CP3 (C) CP4 (S) (X09-)		VR3 (C) VR4 (S) (X09-)	10mV~13.2mV	
2	PRO LOGIC S-OUT NOISE LEVEL	Short CN11 (X11-) (B/5) Short CN10 (X11-) (E/5)	Connect a oscilloscope Rear sp L or R. (Connect load with Rear sp L and R.)	Volume : MAX REAR LEVEL : MAX	VR3 (X11-) (B/5)	Minimum noise level (fig. © point of (b).	(b)







WIRING DIAGRAM


PC BOARD (COMPONENT SIDE VIEW)


CONTROL UNIT

XII-350X-XX C/5 (KA-894:0-II, 994:0-I0, V3700:2-71)











PC BOARD (COMPONENT SIDE VIEW)

CONTROL UNIT

XII-350X-XX A/5 (

-71)





PC BOARD (COMPONENT SIDE VIEW) AUDIO UNIT (a) IDLE CURRENT (CP1,2): 13.2mV (CP3,4): 10mV ~ 13.2mV W145 C220 R218 Oscilloscope (2) PRO LOGIC S-OUT NOISE LEVEL : R319 Minimum noise level W53 W52 SPEAKERS (CENTER) X09-3970-10 C/5 125V 6A AC110-250V WH25O LILL WH24 □ ←O 0 **≣O→** X09- A/5 X09- B/5 ¹/₀ → X09- D/5 LIO 08 Ø 810 X09- E/5 610 OZ0 LINE OUT PHONES 120 C39 C40 OSS 12. R42 OS3 5 🛛 R41 770 POWER SUPPLY F3 | 0 25 \bigcirc

22



ANODE CONNECTION

	1G	2G	3G	4G	5G	6G	7 G	8G	9G	10G	11G
a	a		a	a	a	a	a	a	а	a	a
b	ь		b	ь	ь	ь	b	b	b	ь	ь
С	С		С	С	С	С	С	С	С	С	С
d	đ		d	d	đ	d	đ	d	d	d	d
е	е		е	е	6	е	е	е	9	е	9
f	1		f	f	f	f	ı	f	f	f	f
9	g		g	g	g	g	9	g	g	g	g
h	h		h	h	h	h	h	h	h	h	h
i	i	LOUDNESS	i	i	i	j	j	i.	j	j	ì
k	k	LINE STRAIGHT	k	k	k	k	k	k	k	k	k
Е	MUTING	TAPE2	m	m	Э	m	m	m	m	m	m
n	3 STEREO	V2	n	n	n	n	n	n	n	п	n
P	SURROUND	V1	р	р	р	р	р	Р	р	Р	Р
r		ms	ſ	r	r	r	ſ	r	ľ	ľ	r
s	S	dB						_		_	_
1		0		T				1		1	

MODEL NAME	UNIT NAME	C69,70	D204	D205
	X11-3500-10		YES	YES
KA-894	X11-3500-11	NO	NO	NO
KA-V3700	X11-3502-71	YES	YES	NO

IC5-7 : NJM4558D IC16 : TC9212P IC17 : TC9215P IC18 : CXP82320-162Q IC19 : S-80740AL

Q1~4 : 2SC1740S(Q,R) or 2SC2785(F,E)


D201~224 : 1SS133 or HSS104 D316 : RD5.6ES(B2) or HZS5.6N(B2) D317 : B30-2461-05


D318,319 : RD13ES(B2) or HZS13N(B2)

A1 : W02-1174-05/W02-1188-05/ W02-1046-05


ED1 : FIP11SM8R

	SIGN	AL LINE
	GND	LINE
	+8	LINE
	-8	LINE






AD



• DC voltages are as measured with a high impedance voltmeter. Values may vary slightly due to variations between individual instruments or/and units

CAUTION: For continued safety, replace safety critical components only with manufactist). Indicates safety critical components. To reduce the risk of electors ock, leakage-curre out (exposed parts are acceptably insulated from the supply circuit) bore—the appliance is re





ufacturer's recommended parts (refer to parts urrent or resistance measurements shall be carried a returned to the customer.

and the second s

KA-894/994/V3700 KENWOOD

0






CAUTION: For continued safety, replace safety critical components only with manufacturer's recommended parts (refer to carts list). A Indicates safety critical components. To reduce the risk of electric shock, leakage-current or resistance measurements shall be carried out (exposed parts are acceptably insulated from the supply circuit) before the appliance is returned to the customer.

KA894/994/V3700

EXPLODED VIEW (UNIT)



PARTS LIST

TR T	\perp												
Destination			××××	9.7×7.5 X.7×	a ože	EE>XX	×	ž		A X		-	
Description 数 品 化 / 斯 在	BINDING	NETALLIC CABINET PRESSING PANEL REMOTE CONTROLLER ASY RC-50800	DRESSING PLATE WARRANTY CARD WARRANTY CARD WARRANTY CARD WARRANTY CARD	HARRANTY CARD CAUTION CARD CAUTION CARD CAUTION CARD CAUTION CARD CAUTION CARD CAUTION CARD PL (PTX TYPE)	CAUTION CARD PL (R TYPE) INSTRUCTION MANUAL (F) INSTRUCTION MANUAL (F) INSTRUCTION MANUAL (SP) INSTRUCTION MANUAL (SP)	AC PLUC ADAPTER AC POWER CORD AC POWER CORD AC POWER CORD AC POWER CORD	FLAT CABLE 29P XII CNI-XII CN9 FLAT CABLE 27P XII CN2-X09 CN1 AC QUTLET	INSULATING BOARD INSULATING SHEET INSULATING SHEET	CUSHIGN	ITEM CARTON CASE ITEM CARTON CASE POULYSTYRENE FOAMED FIXTURE (L) POLYSTYRENE FOAMED FIXTURE (R) CARTON BOARD	PROTECTION BAG (235X350X0.03) PROTECTION BAG	FOUT PIA UNITHULDER POWER CORD BUSHING WIRE BAND	KNOB (BASS/TREBLE) KNOB (SURROUN) KNOB (FOWER/SPEARES) KNOB (MAK)
Parts No. 电由中中	N08-0128-35	A01-3098-11 A21-1855-03 A60-0540-11 A70-0974-05 A09-0170-08	B03-2890-23 B46-0092-33 B46-0094-03 B46-0095-03 B46-0096-43	846-0121-33 B58-0513-04 B58-0964-03 B58-0965-03 B58-0966-03	B58-0970-03 B60-1504-00 B60-1505-00 B60-1506-00 B60-1506-00	E03-0115-05 E30-2592-15 E30-2605-05 E30-2650-05 E30-2717-05	G35-0766-05 E35-0767-05 G03-0141-05	F20-1284-05 F20-1297-05 F20-1393-04	610-0173-04	H50-0961-04 H50-0996-04 H10-5676-02 H10-5677-02 H13-0147-14	H25-0232-04 H25-1516-04	J02-0366-;5 J12-0091-15 J19-3657-;4 J42-0083-05 J61-0307-05	K29-5838-04 K29-5849-02 K29-5850-03
New Parts		**	*		****		* *	*		* *	*	*	* * *
Address the H	10	1A 2A 1A 1A	2 A			10 10 10	2B 1A 1C	201 100 180	20			28,20 10 18 18 10	2A 2A, 2B
Ref. No. 卷頭軸如		601 602 603 604 605	610	, , , , , ,		615 616 616 616 616	617 618 J11	621 622 623	624			625 626 627 632	635 637

P:Canada

K:USA T:England X:Australia

L:Scandinavia Y:PX(Far East, Hawaii) Y:AAFES(Europe)

7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	Desti- Re- nation marks 仕 向 審考			[]	ш ш		F		⊢ ш	<u>⊢ ≅ m ⊢ ⊱</u>			.a.⊱	
## ## ## ## ## ## ## ## ## ## ## ## ##	Description 品名/独	00 (FRANCE MADE)	CABINET PANEL COVER	PL (PTX TYP	PL (ELM TYPE ANUAL (EN) ANUAL (F/G/D/I	OWHER CORD POWER CORD T CABLE 29P X11 CN1-X11 CN F CABLE 27P X11 CN2-X09 CN	NSULATING B NSULATING S NSULATING S NSULATING B	CUSHION	CASE CASE FOAMED FIXTURE (L. FOAMED FIXTURE (R	D BAG (235X350 BAG (0232 PR BAG (0361 PR	HOLDER CORD BAND	00000 00000 00000	OWER	INDIG HEAD TAPTITE SCREW INDING HEAD TAPTITE SCREW INDING HEAD TAPTITE SCREW EXAGON HO TAPPING SCREW MAIN AP SCREW WITH WASHER MAXIA
Address	Parts No.	KA-V37	-3098-1 -1855-0 -0541-2 -0974-0	3-2890-2 5-0287-0 5-0310-0 3-0945-0	58-0966-0 60-1508-0 60-1509-0	30-2592-1 30-2721-0 35-0766-0 35-0767-0 03-0085-0	20-1284-0 20-1297-0 20-1393-0 20-1258-0	-0173-0	0998-04 0999-04 -5738-02 -5739-02	3-0148-04 5-0232-04 5-0361-04 5-0651-04 5-066-04	-1040-0 -0091-1 -3657-1 -0083-0	29-5838-0 29-5849-0 29-5850-0 29-5851-0 29-5866-0	07-0876-0 07-0877-0	-2608-4 -3008-4 -3008-4 -0333-0
# H H H H H H H H H H H H H H H H H H H			**	*	* *	**	* *		****	*	*	***	* *	
	Address 在 在 直		18 28 18 18	2 A A		11 2 B C C	20 m	3c			മാമാ	.5		44000

KA894/994/V3700

A indicates safety critical components

Y:PX(Far East, Hawaii) Y:AAFES(Europe)

PARTS LIST

	画 arks		-												
Desti-	# #				×>>×	A X X X X X X X X X X X X X X X X X X X	α d.Ε.Σ	J.E.E.	EE>XXX	×	ž		K A X		
Description	哲 昭 名/燕 祐	HEXAGON HD TAPPING SCREW M3X12 TAP SCREW WITH WASHER M3X14 BINDING HEAD TAPTITE SCREW TAPTITE SCREW (EARTH)	(SINGAPORE MADE)	METALLIC CABINET DRESSING PANEL PANEL REMOTE CONTROLLER ASY RC-ROBO1 BATTERY COVER	DRESSING PLATE WARRANTY CARD WARRANTY CARD WARRANTY CARD WARRANTY CARD	WARRANTY CARD CAUTION CARD (CAUTION CARD CAUTION CARD CAUTION CARD CAUTION CARD CAUTION CARD PL (PTX TYPE)	CAUTION CARD PL (R TYPE) INSTRUCTION MANUAL (F) INSTRUCTION MANUAL (F) INSTRUCTION MANUAL (SP) INSTRUCTION MANUAL (SP)	I/MANUAL PRESET RC (EN) I/MANUAL PRESET RC (F) I/MANUAL PRESET RC (SP) I/MANUAL PRESET RC (C)	AC PLUG ADAPTER AC POWER CORD AC POWER CORD AC POWER CORD AC POWER CORD	FLAT CABLE 29P X11 CN1-X11 CN9 FLAT CABLE 27P X11 CN2-X09 CN1 AC ØUTLET	INSULATING BOARD INSULATING SHEET INSULATING SHEET	CUSHION	ITEM CARTON CASE ITEM CARTON CASE POULYSTYRENE FOAMED FIXTURE (L) CARTON BOARD	PROTECTION BAG (235X350X0.03) PROTECTION BAG	
Parts No.	() () ()	N09-0333-05 N09-2907-05 N89-3018-46 N09-2909-05	KA-994	A01-3098-11 A21-1855-03 A60-0539-11 A70-0961-05 A09-0169-08	B03-2890-23 B46-0092-33 B46-0094-03 B46-0095-03 B46-0096-43	B46-0121-33 B58-0513-04 B58-0964-03 B58-0965-03 B58-0966-03	B56-0970-03 B60-1500-00 B60-1501-00 B60-1502-00 B60-1503-00	B60-1595-00 B60-1596-00 B60-1597-00 B60-1598-00	E03-0115-05 E30-2592-15 E30-2605-05 E30-2650-05 E30-2717-05	E35-0766-05 E35-0767-05 E03-0141-05	F20-1284-05 F20-1297-05 F20-1393-04	610-0173-04	HSO-0958-04 HSO-0959-04 HIO-5676-02 HIO-5677-02 HI3-0147-14	H25-0232-04 H25-1516-04	
N S	*			**	*		***			* *	*		* *	*	_
Address	包置	51 51 118 51		18 28 18 18	2A				4 5555	2B 1A 1C	10 10 18	2C	- 11111		
Ref. No.	参照者与	OEOI.		601 602 603 604 605	610	1111	1111		615 616 616 616 616	617 618 J11	621 622 623	624		F 1	
									বৰবৰৰ						_

Desti- Re- nation marks 在 包 審心	×>×±	2		0	****	ж <u>ъ</u> ж	6.						2. X	
Description 夢品 名/婉 祐	POWER TRANSFORMER POWER TRANSFORMER POWER TRANSFORMER POWER TRANSFORMER	BINDIG HEAD TAPTITE SCREW BINDING HEAD TAPTITE SCREW BINDING HEAD TAPTITE SCREW HEXAGON HD TAPPING SCREW MAXI TAP SCREW WITH WASHER MAXIA	AD TAPTITE	METALLIC CABINET DRESSING PANEL REMAINE REMOTE CONTROLLER ASY RC-S08000 BATTERY COVUER	DRESSING PLATE WARRANTY CARD WARRANTY CARD CAUTION CARD CAUTION CARD CAUTION CARD	CAUTION CARD PL (R TYPE) INSTRUCTION MANUAL (EN) INSTRUCTION MANUAL (F) INSTRUCTION MANUAL (SP)	AC POWER CORD FLAT CABLE 29P XII CNI-XII CN FLAT CABLE 27P XII CN2-X09 CN	INSULATING BOARD INSULATING SHEET	CUSHION .	ITEM CARTON CASE POLYSTYRENE FOAMED FIXTURE (L. POLYSTYRENE FOAMED FIXTURE (R. PROTECTION BAC (235X350X0.03) PROTECTION BAC	FOOT PIN UNIT HOLDER POWER CORD BUSHING WIRE BAND	KNOB (BASS/TREBLE) KNOB (SUKROUND) KNOB (VOLUME (SONTROL) KNOB (VOLUME (SONTROL) KNOB (INPUT SELECTOR)	POWER TRANSFORMER POWER TRANSFORMER	BINDING HEAD TAPTITE SCREW BINDING HEAD TAPTITE SCREW
Parts No.	L07-0845-05 L07-0846-05 L07-0847-05 L07-0847-05	N82-2608-46 N89-3008-45 N89-3008-46 N09-0333-05 N09-2907-05	N89-3018-46 N09-2909-05	A01-3098-11 A21-1855-03 A60-0540-11 A70-0974-05 A09-0170-08	B03-2890-23 B46-0092-33 B46-0121-33 B58-0964-03 B58-0965-03	B58-0970-03 B60-1504-00 B60-1505-00 B60-1506-00	E30-2650-05 E35-0766-05 E35-0767-05	F20-1284-05 F20-1297-05	G10-0173-04	H50-0997-04 H10-5680-02 H10-5681-02 H25-0232-04 H25-1516-04	302-0366-15 312-0091-15 319-3657-14 342-0083-05 361-0307-05	K29-5838-04 K29-5849-02 K29-5850-03 K29-5851-04 K29-5866-04	L07-0843-05 L07-0847-05	N89-3008-15 N89-3008-15
Perts	**			**	*	***	**			*** *	*	* * *		~
Address 12 III	18 18 18 18	1A, 2B 1A, 1C 1C, 2C 1C	18 10	28 28 18 18	2 A		1C 2B 1A	10	3C		28,20 10 18 18	22 A 2 2 B 2 A 3 2 B	30.00	(1, 10)
Ref. No.	244 234 235 24			601 602 603 604 605	10		16 17 18	21 22	24		25 26 32 32	3988736	S. S.	

PARTS LIST

A indicates safety critical components

P.Canada E.Europe M.Other Areas

Y:PX(Far East, Hawaii) Y:AAFES(Europe)

Re-marks											·		
Desti- nation 任 向		R d							YMXTE KPR				YMXTE
梅			CREW SCREW SCREW REW M3X12 M3X14	SCREW		2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Z 50WV 3 J 6.3WV	υς 16¥ 1	24552	2 100WV 3 2 50WV	7 7 6.34V	ر د د 1697 ن	2.2.2.5.2.5.2.5.0.0.0.0.0.0.0.0.0.0.0.0.
Description 品名/規	(SURROUND) (POWER/SPEAKERS) (VOLUME CONTROL) (INPUT SELECTOR)	TRANSFORMER TRANSFORMER	HEAD TAPTITE SCREW G HEAD TATITE SCREW C HEAD TAPTITE SCREW N HD TAPPING SCREW M3) REW WITH WASHER M3X14	HEAD TAPTITE SCREW (EARTH)	(XX-X9)	2.20F 2.20F 0.10F 4700PF 0.010UF	0.010UF 1.0UF 1000PF 100PF 220UF	68PF 2.0PF 68PF 22UF 220PF	0.010UF 4700PF 0.22UF 0.10UF 4700PF	0.0100F 470F 100PF 0.0100F 1.00F	1000PF 220PF 100PF 220UF 100UF	68PF 68PF 68PF 22UF 220PF	0.010UF 4700PF 0.22UF 0.10UF
13	KNOB (SURR KNOB (POVE KNOB (VOLU KNOB (INPU	POWER TRAN	BINDIG HEA BINDING HE BINDING HE HEXAGON HD	BINDING HE TAPTITE SC	XX-X962-396X-XX	ELECTRO BLECTRO ELECTRO CERAMIC CERAMIC	CERAMIC ELECTRO MYLAR CERAMIC ELECTRO	CERAMIC CERAMIC CERAMIC BLECTRO	CERAMIC CERAMIC MF MF CERAMIC	CERAMIC ELECTRO CERAMIC CERAMIC BLECTRO	MYLAR CERAMIC CERAMIC ELECTRO	CERAMIC CERAMIC CERAMIC ELECTRO	CERAMIC CERAMIC MF MF
Parts No. 部品書号	K29-5849-02 K29-5850-03 K29-5851-04 K29-5866-04	L07-0871-05 L07-0872-05	N82-2608-46 N89-3008-45 N89-3008-46 N09-0333-05 N09-2907-05	N89-3018-46 N09-2909-05	KA-894/V3700 AUDIO	CE04LW1H2R2R CE04LW1H2R2M CE04LW1H0R1M CK45FF1H472Z CK45FF1H103Z	CK45FF1H103Z CEO4LW1H010M CQ92FM1H102J CC45FSL1H101J CEO4LW03221M	CC45FSL1H680J CC45FSL1H020C CC45FSL1H680J CE04LW1C220M CC45FSL1H221J	CK45FF1H103Z CK45FF1H472Z CF92FV1H224J CF92FV1H104J CK45FF1H472Z	CK45FF1H103Z CEO4UWZA470M CC45FSL1H101J CK45FF1H103Z CEO4LW1H010M	CQ92FM1H102J CC45FSL1H22JJ CC45FSL1H1013 CE04LW0J22IM CE04LW1A10IM	CC45FSL1H680J CC45FSL1H020C CC45FSL1H680J CE04LW1C220M CC45FSL1H221J	CK45FF1H103Z CK45FF1H472Z CF92FV1H224J CF92FV1H104J CF0ALW2AAD2M
New Parts	* * *	* *										- ·· · · · · · · · · · · · · · · · · ·	
Address 位 富	2A 2A, 2B 2A 2A	9 8	1A, 2B 1A, 1C 1C, 2C 1C	# 21									
Ref. No.	636 637 639 639	645 645	▼™ ∪○ ™	9 =		01 ,2 011 012 039 ,40	C101, 102 C103, 104 C105, 106 C107, 108 C109, 110	C111,112 C113,114 C115,116 C117,118	C121, 122 C123, 124 C125-128 C125, 126 C129, 130	C131 C135, 136 C151, 152 C201, 202 C203, 204	C205 C206 C207, 208 C209 C210	C211, 212 C213, 214 C215, 216 C217, 218 C219, 220	C221,222 C223,224 C225-228 C225,226

PARTS LIST

* New Parts
Parts without Parts No. are not supplied
Parts or mentiornes dans le Parts No. ne sont pas fournis.
Taile Arno Parts No. warden nicht naliefart

æ.	marks ##												
Desti-	nation 仕向向	TE	3E 3E					Y XPX				X X X X X X X X X X X X X X X X X X X	
				504V 504V	2 2 2 2	Z Z 550WV J	6.3WV 5 C 5 1 16WV	78877	Z 100WV J 2	50WV J 10WV J	c J 16WV J Z	Z J J 100WV	16WV 6.3WV 100WV 16WV 6.3WV
Description	名/海布			2.2UF	0.10F 4700PF 0.010UF	0.010UF 0.010UF 1.0UF 1000PF 100PF	2200F 68PF 2.0PF 68PF 22UF	220PF 0.010UF 4700PF 0.22UF 0.10UF	4700PF 0.010UF 47UF 100PF 0.010UF	1.0UF 220PF 100PF 100UF 68PF	2.0PF 68PF 22UF 220PF 0.010UF	4700PF 0.10UF 0.22UF 0.22UF 4.7UF	2200F 2200F 470F 1000F 4700F
۵	48 €	TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR	TRANSISTOR TRANSISTOR TRANSISTOR	UNIT (XOB-387X-XX) ELECTRO	ELECTRO CERAMIC CERAMIC	CERAMIC CERAMIC ELECTRO MYLAR CERAMIC	ELECTRO CERAMIC CERAMIC CERAMIC ELECTRO	CERAMIC CERAMIC CERAMIC MF	CERAMIC CERAMIC ELECTRO CERAMIC CERAMIC	ELECTRO CERAMIC CERAMIC ELECTRO CERAMIC	CERAMIC CERAMIC ELECTRO CERAMIC CERAMIC	CERAMIC MF MF MF ELECTRØ	ELECTRO ELECTRO ELECTRO ELECTRO
Parts No.	中中国	2SC2003(L,K) 2SC2003(L,K) 2SC2003(L,K) 2SB1370 2SB1375	2SC1845(F,E) 2SA992(F,E) 2SC1845(F,E)	KA - 804 AUDIO 1LW1H2R2M	CEO4LW1HOR1M CK45FF1H472Z CK45FF1H103Z	CK45FF1H103Z CK45FF1H103Z CE04LW1H010M CQ92FM1H102J CC45FSL1H101J	CEO4LW0J221M CC45FSL1H680J CC45FSL1H020C CC45FSL1H680J CEO4LW1C220M	CC45FSL1H2213 CK45F1H103Z CK45F1H472Z CF92FV1H224J CF92FV1H104J	CK45FF1H472Z CK45FF1H103Z CE04LW2A470M CC45FSL1H101J CK45FF1H103Z	CEO4LW1H010M CC45FSL1H221J CC45FSL1H101J CEO4LW1A101M CC45FSL1H680J	CC45FSL1H020C CC45FSL1H680J CE04LW1C220M CC45FSL1H221J CK45FF1H103Z	CK45FF1H472Z CF92EV1H104J CF92EV1H224J CF92EV1H224J CE04LW2A4R7M	CED4LW1C220M CEO4LW0J221M CEO4LW2A470M CEO4LW1C101M CEO4LW1C101M
Ne.	Parts Res												
Address	A												
Ref. No.	物医毒丸	045 ,46 049 051 052 052	953 955 956		C12 C39 ,40	C45 ,46 C101,102 C103,104 C105,106 C105,106	C109, 110 C111, 112 C113, 114 C115, 116 C117, 118	0119,120 0121,122 0123,124 0125-128 0125,126	C129, 130 C131 C135, 136 C151, 152 C201, 202	C204 C206 C208 C210	C214 C216 C218 C220 C222	C224 C226 C226 C228	C230 C231 C232,233 C236 C237

0110 0110 0114,115 0114,115

D116 D117 D117 ICS ICS IC7 IC7 Q1 ...2 Q3 ...6 Q1 ...12 Q11 ...12 Q11 ...12 Q13 ...14

D35 D101 D102 D103, 104 D103, 104 D107, 108 D107, 108

ৰৰ ৰৰৰ

,26 ,26

020 020 025 025 035

P.Canada R: Mexico E:Europe M:Other Areas T:England X:Australia Y:PX(Far East, Hawaii) Y:AAFES(Europe) LScandinavia

A indicates safety critical components

R: Mexico

E:Europe M:Other Areas P:Canada

T:England X:Australia KUSA

L:Scandinavia Y:PX(Far East, Hawaii) Y:AAFES(Europe)

indicates safety critical components.

€

44

919,20 921,22 923-26 927-30 931,32 033 033 037 040

4 % 8 8

* New Parts
That without Parts No. are not supplied
Les articles non mentionnes dans le Parts No. ne sont pas fournis.
Telle ofnne Parts No. warden nicht geliefert.

参照者与

Ref. No.

indicates safety critical components.

R: Mexico

M:Other Areas P:Canada

X:Australia K:USA

Y:PX(Far East, Hawaii) Y:AAFES(Europe) L:Scandinavia

A X X X B

PHASE COMPENSATION COIL
POWER TRANSFORMER
POWER TRANSFORMER
POWER TRANSFORMER
POWER TRANSFORMER

L39-0085-05 L07-0864-05 L07-0865-05 L07-0866-05 L07-0866-05

CLIP CLIP CLIP CLIP CLAMPER

FUSE FUSE FUSE FUSE WIRE

J13-0075-05 J13-0075-05 J13-0075-05 J13-0075-05 J11-0098-05

CN11,12 CN13,14 CN15,16 CN21,22 JB ,9

F05-2525-05 F05-2525-05 F05-6029-05 F05-3121-05 F04-2025-05

E03-0148-05

306-2021-05

35

0.22

PAN HEAD MACHINE SCREW

9

PARTS LIST

i-Re- n marks 向傳考		Ž			×	PYMXR E PYMXR	XX	KPYMXR KPYMXR	M.X.		
Destination		KPYMXF	15	2	KPYMXF	X T X	TE TE KPYMXA TE	KPY KPY	KPYMXF TE YM	→ +	
	2W 1/4W 1/4W 1/4W 1/4W	1/4W 2W 1/4W 1/4W 1/4W	1/4W 1/4W 1/4W 1/4W	1/4W 2W 1/4W 2W 1/4W	1/4W 1/4W 1/4W 1/4W	1/4% 1/4% 1/4% 1/4%	1/4W 1/4W 1/4W 1/4W		SEL)	SEL.)	
犇	ממממט	20225	20202	היהוחים	המהנהנ	22220	טטטט		VOLTAGE VOLTAGE	VOLTAGE IPEDANCE	
Description 品名/規	560 220 270 220 22	8.2K 10 10 10 10	22 220 270 220 22	8.2K 10 10 3.3K 1.0K	820 2.2 10 4.7 2.2	10 100 560 680 150	820 1.0K 820 15	*****	A C	S T	
# 0°s	RS .	. RS		S S			Por	C RELAY C, RELAY C, RELAY C RELAY	C RELAN C RELAN C RELAN WITCH	SWITCH	9
	L-PROOF	RD FL-PROOF RD FL-PROOF RD	880 880 80 80 80 80 80 80 80 80 80 80 80	RD FL-PRØØF RD FL-PRØØF RD	88888 88888	22222 20222	RD RD RD RD TRIMMING	MAGNETI MAGNETI MAGNETI MAGNETI MAGNETI	MAGNETIC MAGNETIC MAGNETIC SLIDE SWI SLIDE SWI	SLIDE S	D100E D100E D100E D100E
	E & & & &	<u> </u>	~~~~~	****	*****						
arts No. An min sp	30561J 26221J 26271J 26221J 26221J	26822J 3D100J 2E100J 2E100J	B2E220J B2E221J B2E271J B2E221J B2E220J	2E822J 3D100J 3ZE100J 3D332J 3E102J	32E821J 32E2R2J 32E100J 32E4R7J	82E100J 82E101J 82E561J 82E681J 82E681J	32E821J 32E102J 32E821J 82E150J 616-05	2078-05 2092-05 0005-05 0016-05	002-05 009-05 036-05 001-05 322-05	001-05 034-05	04A 31. 04 33
. 188 F. 188	RS14KB3DE RD14NB2E2 RD14NB2E2 RD14NB2E2 RD14NB2E2	RD14NB RS14KB RD14NB RD14CB RD14CB	RD14NB RD14NB RD14NB RD14NB RD14NB	RD14NB RS14KB RD14NB RS14KB RD14NB	RD14NB RD14NB RD14NB RD14NB RD14NB	RD14NE RD14NE RD14NE RD14NE RD14NE	RD14NB RD14NB RD14NB RD14NB RD14NB	S51-2 S51-2 S76-0 S76-0	\$76-00 \$76-00 \$76-00 \$76-00 \$62-00	\$62-0 \$62-0	HSS10 1SS13 HSS10 1SS13
S tr											
Address (½)						-					
. or	118 118 124 136	142	224 224 226 240	244 254 254	,308	,313 ,320	7				-14 -14 -14
Ref. ∰	R41 R117, R123, R125, R135	R141, R145, R151 R152	R155 R217 R223 R225 R237	R247 R253 R253 R270 R285	R285 R303 R304 R307 R309	R312 R314 R319 R319	R321 R322 R322 R323 VR1	X X X X X X X X X X X X X X X X X X X	8 X X X X X X X X X X X X X X X X X X X	S3	03 03 03

fournis.		•	* 6.7 14	 New Parts Parts without Parts No. are not supplied. Les articles non mentionnes dans le Parts N Teile ohne Parts No. werden nicht geliefert. 	ts No. are n nentionnes No. werden	oot su dans nicht	ipplied. Ie Parts N geliefert.
Description	Desti-	% S	-	Ref. No.	Address	ž ;	Part
節 语 名/然 箱	the ballon	marks 条 外		参照番号	₩	2 Mag	₩2 ₩2
ELECTRO 22UF 16WV ELECTRO 220UF 6.3WV ELECTRO 47UF 100WV ELECTRO 100UF 6.3WV				R41 ,42 R117,118 R123,124 R125,126 R135-138			RS14KB3 RD14NB2 RD14NB2 RD14NB2 RD14NB2
NP-ELEC 2.2UF 50WV CERANIC 4700PF 2 CERANIC 0.010UF 2 BLECTR® 47UF JOWV CERANIC 100FF J				R141,142 R145,146 R151 R152 R155			RD14NB2 RS14KB3 RD14NB2 RD14GB2 RD14NB2
ELECTRO 100UF 10WV MF 0.10UF J ELECTRO 470UF 35WV CERANIC 0.010UF 2				R155 R217, 218 R223, 224 R225, 226 R237-240			RD14NB2 RD14NB2 RD14NB2 RD14NB2 RD14NB3
ELECTRO 2200UF 35WV CERAMIC 0.010UF Z M 0.10UF Z ELECTRO 330UF 16WV CERAMIC 0.010UF Z				R243,244 R247,248 R253,254 R270 R285			RD14NB RS14KB RD14NB RS14KB RS14KB
CERAMIC 0.010UF P MYLAR 0.010UF 3 ELECTRO 6800UF 71NV ELECTRO 4.7UF 55WV ELECTRO 47UF 65WV	KPYMXK		44	R285 R303 R304 R307, 308 R309, 310			RD14NB RD14NB RD14NB RD14NB RD14NB
ELECTRO 470UF 35WV CERAMIC 0.010UF Z							RD14NB RD14NB
PHONE JACK (3P) PHONES PHONE JACK (3P) PHONES LOCK TERMINAL BOARD FRT/SUR SI LOCK TERMINAL BOARD CENTER SP AC AUTHER	KPYMXR TE Te	<u> </u>		R319, 320 R319, 320 R321 R321			RD14NB RD14NB RD14NB
	KPYR			R322 R323			RD14NB RD14NB
FUSE (SEMKØ) (250V T2.5AL) FUSE (SEMKØ) (250V T2.5AL) FUSE (UL) FUSE (UL) FUSE (UL) FUSE (UL) (250V T3.15A) FUSE (UL) (250V 24)	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX			7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			\$51-20 \$51-20 \$51-20 \$76-00 \$76-00
FUSE (SEMKO) (250V T2AL) FUSE CLIP	YMXTE	-	44				876-00 876-00

CE04LW1V222M CK45FF1H103Z CF92FV1H104J CE04LW1C331M CK45FF1H103Z

C314,315 C317,318 C320-323 C324,325 C327,328

CK45FE2H103P CQ93HP2A103J C90-3536-05 CE04LW1V4R7M CE04LW1J470M

C331-334 C335-338 C339,340 C341 C342

CE04LW1V471M CK45FF1H103Z

C343 C345,346

E11-0127-05 E11-0190-05 E70-0048-05 E20-0236-05 E03-0149-05

CE04LW1A101M CF92FV1H104J CE04LW1V471M CK45FF1H103Z C91-1488-05

C302, 303 C302, 303 C304 C305-308 C309, 310

CE04HW1H2R2M CK45FF1H472Z CK45FF1H103Z CE04LW2A470M CC45FSL1H101J

C238 C241 C242 C243,244 C251,252

CE04LW1C220M CE04LW0J221M CE04LW2A470M CE04LW1C101M CE04LW0J471M

C230 C231 C232,233 C236 C236

Parts No. 幸福

Address New Parts

Ref. No.

Parts without Parts No are not supplied to satisfications non mentionnes dans to Parts No, ne sont pas founds. Telle otne Parts No, warden nicht geliefert.

andinavia	K:USA	P:Canada R: Mexico	R: Mexico	
X(Far East, Hawaii)	T:England	1 EEurope		
AFES(Europe)	X:Australia	M:Other Areas	as.	⚠ indicates safety critical components.

R: Mexico		reas
P:Canada	E:Europe	M:Other A
	T:England	_
L:Scandinavia	Y:PX(Far East, Hawaii)	Y:AAFES(Europe)

PARTS LIST

* New Parts
Parts without Parts No. are not supplied.
Les articles non mentionnes dans le Parts No. ne sont pas fournis.

Desti	Ħ		> >	> >		>	88	26	<u>}</u>	>		
:	ŧ	7 7 3 3 3 3 4 4 4 7	3 354V 5 0	3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	50WV J 35WV J	D D S E D S E S E S E S E S E S E S E S	254V 2254V 2254V	J 254V 354V J 104V	38WV 38WV 38WV 38WV	J 5.5WV 10WV 50WV	חראבר	N J N S
scripti	をなった。	220PF 3300PF 0.012UF 10UF 22UF	220PF 10UF 2.2UF 56PF	10UF 56PF 10UF 22PF 10UF 4.7UF	2.2UF 0.10UF 4.7UF 10UF 220PF	0.056UF 56PF 560PF 10UF 0.039UF	47UF 0.10UF 47UF 0.010UF 100UF	0.10UF 47UF 10UF 100PF 470UF	100PF 56PF 4.7UF 2.2UF 4.7UF	56PF 0.047F 100UF 1UF 0.010UF	0.10UF 1000PF 220PF 100PF 220PF	1000PF 220PF 0.022UF 1UF
ä	9	CERAMIC MF MF ELECTRO	CERAMIC ELECTRO ELECTRO CERAMIC	ECTR RAMI ECTR ECTR ECTR	ELECTRO MF ELECTRO ELECTRO CERAMIC	ME CERAMIC CERAMIC BLECTRO	BLECTRO ME BLECTRO CERAMIC BLECTRO	MF ELECTRO CERAMIC GLECTRO	CERAMIC CERAMIC ELECTRO ELECTRO	CERAMIC BACKUP ELECTRO ELECTRO CERAMIC	MF CERAMIC CERAMIC CERAMIC CERAMIC	CERAMIC CERAMIC CERAMIC ELECTRO
Parts No.	# E	CC45FSL1H221J CF92FV1H332J CF92FV1H123J CE04LW1V100M CE04LW1V220M	CC45FSL1H221J CEO4LW1V100M CEO4LW1H2R2M CC45FSL1H560J	E04LW1V1 C45FSL1H C45FSL1H E04LW1V1 E04LW1V1	CEOALWIH2R2M CF92FVIH104J CEO4LWIV4R7M C90-3244-05 CC45FSLIH221J	CF92FV1H563J CC45FSL1H560J CK45FB1H561K C90-3244-05 CF92FV1H393J	CBO4LW1E470M CF92FV1H104J CE04LW1E470M CK45FF1H103Z CE04LW1E101M	CF92FV1H104J CE04LN1E470M C90-3244-05 CC45FSL1H101J CE04LN1A471M	CC45FSL1H101J CC45FSL1H560J CE04LW1V4R7M CE04LW1H2R2M	CC45FSL1H560J C90-1827-05 C90-3222-05 C90-3253-05 CK45FF1H103Z	CF92FV1H104J CK45FB1H102K C91-0749-05 CC45FSL1H101J CC45FSL1H221J	CK45FB1H102K CC45FSL1H221J C91-0085-05 C90-3253-05
New Parts	5											
Address												
Ref. No.		C9 ,10 C11 ,12 C13 ,14 C15 ,16 C17 ,18	C19 -36 C37 ,38 C39 ,40 C41 ,42	4 4 4 4 10 10	CSS . 56 CS9 . 60 C61 . 62 C63 . 64	C67 , 68 C69 , 70 C71 , 72 C73 -76 C77 , 78	C100 C101 C102-106 C107,108 C109,110	C111,112 C113-118 C119,120 C151 C152,153	C154 C173,174 C175,176 C177,178 C177,18	C181, 182 C201 C202 C203 C204	C205, 206 C207 C208, 209 C210-212 C213	C214 C215 C216-219 C220

Desti- Re-	tion marks 向												
Ö	#												
	#			+5.75V) -15V)	-15V) +15V) +15V)								~
Description	8 名/維			BEGULATOR/	REGULATOR/ REGULATOR/ REGULATOR/]],	STAND BY 220PF
	192	0100E 0100E 0100E 0100E	DIQDE DIQDE DIQDE DIQDE ZENER DIQDE	ZENER DIODE ZENER DIODE ZENER DIODE IC(VOLTAGE F	IC(VOLTAGE IC(VOLTAGE IC(VOLTAGE TRANSISTOR TRANSISTOR	TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR	TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR	TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR	TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR	TRANSISTOR TRANSISTOR TRANSISTOR TRANSISTOR	TRANSISTOR TRANSISTOR TRANSISTOR	CONTROL UNIT (X11-350X-XX)	LED(RED) CERAMIC
Parts No.	***	KBPO2ML-6127 HSS104A 1SS131 S5688 1SR139-100	DSSBA20F03 RBV-602LFA SS688B 1SR139-100 HZS15N(B2)	RD15ES(B2) HZS16N(B2) RD16ES(B2) TA78057S TA79015S	UPC7915HF TA7815S UPC7815AHF 2SC2878(B) 2SA992(F,E)	2SC2632(R, S) 2SA1124(R, S) 2SC4137 2SB1594LB 2SD2449LB	2SC2631(R, S) 2SC2878(B) 2SA992(F, E) 2SA992(F, E) 2SC2631(R, S)	2SC2631(R, S) 2SA1123(R, S) 2SC4137 2SD2255BT 2SB1493BT	2SC1845(F, E) 2SA1175(F, E) 2SA933S(Q, R) 2SA992(F, E) 2SC1845(F, E)	2SC2003(L,K) 2SA1175(F,E) 2SA933S(Q,R) 2SC2003(L,K) 2SC2878(B)	2SC2003(L,K) 2SB1370 2SB1375	A-894/994/V3700	B30-2461-05 CC45FSL1H221J
New Paris	45												
Address	有關												
ģ	**	401 104 108 108	,110 1115 1115		6.2	122	20;		44.	-47			~
Ref.		0103 0103 0107 0107	0109 01109 0114 0116	0116 0117 0117 105 106	106 107 107 03	97 911 913 915	019 021 026 026 028	0.00 0	940 941 943 943	245 849 849 849 850	951 952 952	. []	D317 C1

A indicates safety critical components

M:Other Areas P:Canada E:Europe

K:USA T:England X:Australia

L:Scandinavia Y:PX(Far East, Hawaii) Y:AAFES(Europe)

A indicates safety critical components.

V: KA-V3700

8: KA-894 9: KA-994

P.Canada E.Europe M.Other Areas

A indicates safety critical components.

L:Scandinavia Y:PX(Far East, Hawaii) Y:AAFES(Europe)

PARTS LIST

Re- marks 曲头											
Desti- nation 仕 南							× ×		····	L-1	
	1/48 28 1/48 1/48 1/48	1/4 V 1/4 V 1/4 V 1/4 V 1/4 V	1/4W 2W 1/4W 2W 1/4W	1/4 1/1 1/4 1/4 1/4 1/4 1/4	1/4W 1/4W		SEL) SEL) SEL)				
S 載	فيوهمو	,,,,,,,	הטהטה	שרמית	חה		VOLTAGE VOLTAGE VOLTAGE				
Description 晶名/機	6.2K 10 10 10 150	220 220 220 22	8.2K 10 10 3.3K 2.2	10 4.7 2.2 10 100	820 150 (1K)	A A A Y Y A Y Y	S S S S S S S S S S S S S S S S S S S				
å •4 3	RS 6		8 8 8		POT POT	C RELAY C RELAY C RELAY C RELAY	<u> </u>		IODE IODE	I ODE	
-	-PROOF	20222	RD FL-PRØØF RD FL-PRØØF RO	88888 88888	RD RD TRIMMING TRIMMING	MAGNETIC MAGNETIC MAGNETIC MAGNETIC	MAGNETIC F MAGNETIC F SLIDE SWIT SLIDE SWIT SLIDE SWIT	DIGOE DIGOE DIGOE DIGOE	DIODE DIODE DIODE ZENER D	DIODE DIODE ZENER D ZENER D DIODE	DIODE
	85858	88888	<u> </u>	***	<u> </u>	EEEEE	EEGGG		20000	22000	
Š 🛊	1822J 1100J 1100J	2217 2217 2207 2200	126822J 13D100J 126100J 13D332J 12E2R2J	14NB2E1003 14NB2E4R73 14NB2E2R23 14NB2E1003	12E821J 12E151J 16-05	8-05 2-05 5-05 6-05	2-05 1-05 1-05		82) 82)	(B2)	
Parts	RD14NB2E82 RS14KB3D10 RD14NB2E10 RD14GB2E10 RD14GB2E10	RD14NB2E RD14NB2E RD14NB2E RD14NB2E RD14NB2E RD14NB2E	RD14N82E RS14KB3E RD14NB2E RS14KB3E RD14N82E	RD14NB2E RD14NB2E RD14NB2E RD14NB2E RD14NB2E	RD14NB2E RD14NB2E R12-1616 R12-1616	S51-2076 S51-2092 S76-0006 S76-0016	76-0002- 76-0036- 62-0001- 31-2322- 62-0001-	SS104A SS131 ISS104A SS131 ISS104A	15S131 HSS104 15S133 HZS15N(E RD15ES(E	HSS104A 1SS131 HZS4.7N(B2) RD4.7ES(B2) HSS104	1SS133 HSS104A
Perts	~~~~	~ ~ ~ ~ ~ ~ ~	****	~~~~	~ ~ ~ ~	NNNNN	00000	x-x-x			
Address t											
. or w	142			308 310 313	320			44	-14	-19 -19 -30	-30
Ref.	R141, R145, R151 R152	R218 R224 R226 R238 R240	R244 R248 R254 R270 R303	R307, R307, R312, R314	R319. R321 VR1 , VR4	22225 22225	X X X X X X X X X X X X X X X X X X X	10000	08 09 09 015	016 016 020 020 025	025 035
							€ €€€				

Ref. No.	Address		Parts No.	Description	_	Desti-	Re-
参照番号	有	165	4 中 中 中	野 唱 令//	损格	_	編集
 C238 C239 C241 C242 C252			CEO4HW1H2R2M CEO4HW1H2R2M CK45FF1H472Z CK45FF1H103Z CC45FSL1H101J	NP-ELEC 2.2UF NP-ELEC 2.2UF CERANIC 4700PF CERANIC 0.010UF CERANIC 100PF	50WV 50WV 3 Z JF Z		
C301 C302,303 C304 C305-308 C309,310			CEO4LW1A101M CF92FV1H104J CEO4LW1V471M CK45FF1H103Z C91-1488-05	ELECTRO 100UF MF 0.10UF ELECTRO 470UF CERANIC 0.010UF MF 6800PF	10WV 35WV JF Z 7 250VAC		
C314,315 C317,318 C320-323 C324,325 C327,328			CEO4LW1V222M CK45FF1H103Z CF92FV1H104J CEO4LW1C331M CK45FF1H103Z	ELECTRO 2200UF CERANIC 0.010UF MF 0.10UF ELECTRO 330UF CERANIC 0.010UF	F 35WV UF 2 F J 16WV UF Z		
C331-334 C335-338 C339,340 C341			CK45FE2H103P CQ93HP2A103J C90-3536-05 CE04LW1V4R7H CE04LW1J470M	CERANIC 0.010UF MYLAR 0.010UF ELECTRO 6800UF ELECTRO 4.7UF ELECTRO 47UF	UF P UF J 714V 354V 634V		
C343 C345,346			CEO4LW1V471M CK45FF1H103Z	ELECTRO 470UF CERAMIC 0.010	F 35WV OUF 2		
511 522 503 703 111			E11-0127-05 E63-0090-05 E70-0048-05 E63-0072-15 E03-0149-05	PHONE JACK (3P) PH PHONG JACK (2P) S. LOCK TERMINAL BOAR PHONG JACK (2P) L/ AC OUTLET	P) PHONES P) S.W/CT PRE OUT BOARD FRT/SUR SP P) L/R LINE OUT	Σ	
513			E03-0148-05	AC OUTLET		KPYR	
F1 F2 F3 F5 F5			F05-252-05 F04-5022-05 F05-2525-05 F05-3121-05 F04-2025-05	FUSE (SEMKØ) (25 FUSE (UL) (12 FUSE (SEMKØ) (25 FUSE (SEMKØ) (25 FUSE (UL) (25	50V T2.5AL) 25V 5A UL) 50V T2.5AL) 50V T3.15AL) 50V 2A)	×××× Eq. xq. xq. xq.	
1.5			F06-2021-05	FUSE (SEMKO) (25	50V T2AL)	ΥWX	
CN11, 12 CN13, 14 CN15, 16 CN21, 22 J8, 9			J13-0075-05 J13-0075-05 J13-0075-05 J13-0075-05 J11-0098-05	FUSE CLIP FUSE CLIP FUSE CLIP FUSE CLIP WIRE CLAMPER		Σ > Σ	
2 3 555			L39-0085-05 L39-0085-05 L07-0864-05 L07-0865-05 L07-0866-05	PHASE COMPENSATION PHASE COMPENSATION POWER TRANSFORMER POWER TRANSFORMER	COIL	X Y X P M R	
Ľ.	18		N30-3008-46	PAN HEAD MACHINE S	SCREW		
CP1 .2 CP4 R41 ,42 R117,118 R123,124			R90-0840-05 R90-0888-05 RS14KB3D561J RD14NB2E221J RD14NB2E271J	RD 0.22 MULTIPLE RESISTOR FL-PROOF RS 560 RD 220 RD 270	5W 3 2W 3 1/4W 3 1/4W		
R125, 126		_	RD14NB2E221J	RD 220	J 1/4W		

P:Canada

L'Scandinavia Y.PX(Far East, Hawaii) Y.AAFES(Europe)

KA-894/994/V3700

PARTS LIST

i- Re-							
Desti-	#	۸6					
Description	邮 品 名/热 格	ICCANALOG SWITCH X 6) ICCANALOG SWITCH X 6) ICCANALOG SWITCH) ICCIGCH BILATERAL SELECTOR SW)	DI BI-POLAR IC IC(ELECTRICAL VOLUME) 1C(ANALGG SWITCH X 6) MI-COM IC IC(VOLTAGE DETECTOR)	IC(ANALGG SWITCH X 6) IC(OP AMP X2) IRMNISTIOR TRANSISTIOR TRANSISTOR	TRANSISTOR TRANSISTOR	ELECTRIC CIRCUIT MODULE ELECTRIC CIRCUIT MODULE ELECTRIC CIRCUIT MODULE	
	a r	20000	629 MI-0				
Parts No.	# 唱	TC9215P NJM2279D NJU7313L TC9164N LA2785	LV1010 TC9212P TC9215P CXP82320-163 S-80740AL	TC9215P NJM4580L 2SC1740S(Q,R) 2SC2785(F,E) 2SD2012	2SD2061(E,F) 2SC2878(B)	W02-1046-05 W02-1174-05 W02-1188-05	
New Part	¥5					*].
Address	台						
ġ	*	- Almm-	2000	1,22			
æf.	#	IC11 IC12 IC13 IC13 IC13	1010	1020 1021 01 01 05	96	A11	

A indicates safety critical components.

V: KA-V3700

8: KA-894 8: KA-994

R: Mexico

M:Other Areas

L:Scandinavia Y:PX(Far East, Hawaii) Y:AAFES(Europe)

PARTS LIST

* New Parts
Parts without Parts No. are not supplied.
Les articles non mentionnes dans le Parts No. ne sont pas fournis.
Telei ofne Parts No. werden nicht geleiert.

9[å	在															
	Desti-			۸6		۸6				226	5	۸6 م	۸۶	۸6			
	Description	部 品 名/挽 格	PHONG JACK (6P) ADPT IN/TAPE PHONG JACK (8P) VI/V2/ADPT GUT PHONG JACK (4P) TUNER/CD INPUT PHONG JACK (2P) PHONG MINIATURE PHONE JACK S.CONTROL	PHONG JACK (4P) M OUT/V1/V2 IN	RESONATOR (10.000MHz) RESONATOR (8MHz)	MULTI-COMP 47K X7 3 1/6W FL-PROOF RD 680 3 1/4W RL PROOF RS 2 3 2W RL PROOF RS 39.0K F 1/6W	POTENTIOMETER(100K X2) TRIMMING POTENTIOMETER(2.2K)	PUSH SWITCH (SURRGUND MODE)	SPEED DETECTOR SPEED DETECTOR	0100E 0100E 0100E 0100E	0100E 0100E 0100E 0100E	0100E 0100E 0100E 0100E	ZENER DIØDE	ZENER DIODE DIODE DIODE ZENER DIODE	ZENER DIQDE ZENER DIQDE ZENER DIQDE ZENER DIQDE DIQDE	DIODE INDICATOR TUBE ICCOP AMP X2) ICCOP AMP X4) ICCOP AMP X2)	ICCOP AMP X2) ICCOP AMP X2) ICCOCH ELECTRONIC VOLUME) ICCOP AMP X2)
	Parts No.	中丰田田田	E63-0047-15 E63-0070-15 E63-0046-15 E63-0068-15 E11-0188-05	E63-0069-15	L78-0294-05 L78-0290-05	R90-0816-05 R90-0487-05 R014GB2E681J RS14KB3D220J RN14BK2C3902F	R10-5076-05 R12-1086-05	S40-1064-05	T99-0547-05 T99-0548-05	HSS104 1SS133 HSS104 1SS133 HSS104	1SS133 HSS104 1SS133 HSS104 1SS133	HSS104 1SS133 HSS104 1SS133	HZS5.1N(82)	RD5.1ES(B2) HSS104 1SS133 HZS10N(B2) RD10ES(B2)	HZS.6N(B2) RD5.6ES(B2) HZS13N(B2) RD13ES(B2) HSS104	15S133 FIP11SM8R NJH4580D-D NJM2058D	NJM4558D NJM4580L TC9213P NJM4580L
ᇎ		**							*								
No. werde	Address	包置															
Ĕ	Ref. No.	李素寿	11 132 144 15	36	×1 ×2	CP1 CP2 R101-104 R113 R319	VR1 ,2 VR3	Si -17	S18 S19	0201-203 0201-203 0204 0204 0205	D205 D206-224 D206-224 D301,302	D303,304 D303,304 D305-310 D305-310	311,	0311,312 0313,314 0313,314 0315	0316 0316 0318-321 0318-321 0322-327	D322-327 ED1 IC1 IC2 IC3	1C4 -7 1C8 1C9 1C10

	marks 未未		· · · · · · · · · · · · · · · · · · ·									
	nation #										۸6	
	垄	J 50WV Z J	2 25WV 35WV 35WV 50WV	164V 504V 504V 164V 504V		354V 504V J 504V J	35WV 50WV 35WV J	25#V J 35#V J	50WV J 35WV 50WV 35WV	50WV J 50WV 16WV 35WV	16WV J Z Z	22
	B か/瀬	0.10UF 10UF 0.010UF 220PF 220PF	0.010UF 47UF 4.7UF 47UF 2.2UF	2200F 4.70F 1.00F 2200F 1.00F	0.10UF 1.0UF 0.033UF 1500PF 0.033UF	10UF 2.2UF 0.15UF 3.3UF 0.15UF	4.70F 0.470F 4.70F 0.470F 0.100F	47UF 0.47UF 10UF 680PF 0.15UF	3.3UF 0.15UF 4.7UF 0.47UF 4.7UF	0.47UF 0.10UF 1.0UF 220UF 10UF	220UF 0.047UF 0.022UF 0.010UF	0.010UF 0.010UF
	128	MF ELECTRO CERAMIC CERAMIC CERAMIC	CERAMIC BLECTRO BLECTRO ELECTRO BLECTRO	BLECTRO GLECTRO GLECTRO GLECTRO BLECTRO		BLECTRO ELECTRO MF ELECTRO	ELECTRO ELECTRO ELECTRO ELECTRO	ELECTRO MF ELECTRO CERAMIC MF	ELECTRO MF ELECTRO ELECTRO ELECTRO	BLECTRO BLECTRO BLECTRO BLECTRO	ELECTRO MF MF CERAMIC CERAMIC	CERAMIC
Darte Mr.	odi.	CF92FV1H104J C90-3258-05 CK45FF1H103Z CC45FSL1H221J C91-0749-05	CK45FF1H103Z CEO4LW1E470M CEO4LW1V4R7M CEO4LW1V470M CEO4LW1H2R2M	CEO4LW1C221M C90-3256-05 CEO4LW1H010M CEO4LW1C221M CEO4LW1H010M	CF92FV1H104J CF92FV1H105J CF92FV1H333J CF92FV1H152J CF92FV1H333J	CEO4LW1V100M CEO4LW1H2R2M CF92FV1H154J CEO4LW1H3R3M CF92FV1H154J	CEO4LW1V4R7M CEO4LW1HR47M CEO4LW1V4R7M CEO4LW1HR47M CF92FV1H104J	CEO4LW1E470M CF92FV1H474J CEO4LW1V100M CK45FB1H681K CF92FV1H154J	CEO4LW1H3R3M CF92FV1H154J CEO4LW1V4R7M CEO4LW1HR47M CEO4LW1V4R7M	CEOALWIHR47M CF92FVIH104J CEO4LWIH010M CEO4LWIC22IM CEO4LWIV100M	CEO4LW1C221M CF92FV1H473J CF92FV1H223J CK45FF1H103Z CK45FF1H103Z	CK45FF1H103Z CK45FF1H103Z
N	2 W											
Address	翘											
, N	2005	C223 C224 C225-229 C230 C231,232	C233 C301-304 C305-307 C308 C309	C310 C311,312 C313 C314 C315	C316 C317 C318 C319	C321 C322 C323 C324 C325	0326 0327 0328 0329 0330, 331	0332 0333 0334-337 0338 0339	C340 C341 C342 C343 C344	C345 C346,347 C348,349 C350 C351-354	0355 0355 0357 0358	C360 C361,362

L.Scandinavia K.U.SA P.Canada R.: Межсо 8: KA-894 V: KA-V3700
Y.P.X(Far East, Hawaii) T.England E.Europe 6: KA-994
Y: AA-FES(Europe) A. Kaustralia M.Other Aveas

41

SPECIFICATIONS

For the USA, Mexico and Canada	For other countries
	ror other countries
AUDIO section	AUDIO section
Rated power output	Rated power output
STEREO MODE (FTC)	STEREO MODE
100 watts per channel minimum RMS, both	(IHF'66) 20 Hz~20 kHz, 0.09%
channels driven, at 8 Ω from 20 Hz to 20 khz with no more than 0.09% total harmonic distortion.	T.H.D. at 8 Ω 100 W + 100 W (EIAJ) 1 kHz, 10%) T.H.D. at 8 Ω 150 W + 150 W
SURROUND MODE	SURROUND MODE
Front	at 8 Ω, 1 kHz, 0.9% T.H.D.
100 watts per channel minimum RMS, both	FRONT
channels driven, at 8 Ω 1 kHz with no more than	NEAN 2U W + 2U W
0.9% total harmonic distortion.	Total harmonic distortion
Rear	
20 watts per channel minimum RMS, both	0.03 % (1 kHz, 50 W, 8Ω)
channels driven, at 8 Ω 1kHz with no more than 0.9% total harmonic distortion.	Frequency response LINE (CD, TAPE, VIDEO) 20 Hz ~ 60 kHz, +0 dB, -3 dB
	PHONO "RIAA" response
Total harmonic distortion 	20 Hz ~ 20 kHz, ± 0.5 dB
0.03% (1 kHz, 50 W, 8 Ω)	Maximum input level
Frequency response	PHONO (MM)120 mV, 0.5% T,H,D, at 1 kHz Signal to noise ratio
LINE (CD, TAPE, VIDEO)	(IHF'66)
20 Hz ~ 60 kHz, +0 dB, -3 dB PHONO "RIAA" response	PHONO(MM) 75 dB
20 Hz ~ 20 kHz, ± 0.5 dB	LINE (CD, TAPE, VIDEO) 95 dB
Maximum input level	Input sensitivity/impedance PHONO (MM)
PHONO (MM) 120 mV, 0.5% T.H.D. at 1 kHz	LINE (CD, TAPE, VIDEO) 200 mV/47 k Ω
Signal to noise ratio (IHF'66)	ADAPTOR IN 200 mV/47 kΩ
PHONO (MM)75 dB	Tone control
LINE (CD, TAPE, VIDEO) 95 dB	BASS \pm 10 dB(at 100 Hz) TREBLE \pm 10 dB(at 10 kHz)
nput sensitivity / impedance	Loudness control (volume at-30 dB level)
PHONO (MM) 3.5 mV / 47kΩ LINE (CD, TAPE, VIDEO) 200 mV / 47kΩ	+8dB (100 Hz)
ADAPTOR IN 200 mV / 47kΩ	Output level/impedance TAPE REC
Tone control	ADAPTOR OUT 200 mV/1 kΩ
### ### ### ### ### ### ### ### ### ##	7.57.0 TOTO OF 1117/ T R.S.
TREBLE \pm 10 dB (at 10 kHz) Loudness control (volume at -30 dB level)	VIDEO section
+ 8 dB (at 100 Hz)	lanut laval/impadance
Output level / impedance	Input level/impedance VIDEO (composite)1 Vp-p/75 Ω
TAPE REC 200 mV /1 kΩ	Input (VIDEO 1, VIDEO 2)
ADAPTOR OUT200 mV / 1 kΩ	Output level/impedance
VIDEO section	VIDEO (composite) 1 Vp-p/75 Ω
	Output (VIDEO 1, MONITOR OUT)
Input level / impedance VIDEO (composite)1 Vp-p/75 Ω	GENERAL
Input (VIDEO 1, VIDEO 2)	
Output level / impedance	Power consumption210 W
VIDEO (composite) 1 Vp-p/75 Ω	AC outlets SWITCHED2; (300 W max.)
Ouput (VIDEO 1, MONITOR OUT)	Dimensions
<i>GENERAL</i>	H: 143 mm
	D: 300 mm
Power consumption2.3 A	Weight (Net)9.3 kg
AC outlets SWITCHED 2: /400 M/ max)	
SWITCHED	
H: 143 mm (5-5/8")	
D: 300 mm (11-13/16") Weight (Net)9.3 kg (20.5 lb)	

Note: KENWOOD follows a policy of continuous advancements in development. For this reason specifications may be changed without notice.


SPECIFICATIONS

(KA-894)

For the USA, Mexico and Canada	For other countries
AUDIO section	AUDIO section
Rated power output (FTC)	Rated power output
STEREO MODE	STEREO MODE
100 watts per channel minimum RMS, both	(IHF'66) From 20 Hz to 20 kHz, 0.09% T.H.D.
channels driven, at 80 from 20 Hz to 20 kHz with	at 8 Ω 100 W + 100 W
no more than 0.09% total harmonic distortion.	(EIAJ)
SURROUND MODE	1 kHz, 10% T.H.D. at 8 Ω 150 W + 150 W
Front	SURROUND MODE
70 watts per channel minimum RMS, both channels	1 kHz, 0.9% T.H.D. at 8 Ω
driven, at 8 Ω 1 kHz with no more than 0.9% total	FRONT 70 W + 70 W
harmonic distortion.	CENTER70 W
	REAR20 W + 20 W
Center	
70 watts at 8 Ω 1 kHz with no more than 0.9% total	Total harmonic distortion
harmonic distortion.	0.06% (20 Hz ~ 20 kHz, 50 W, 8Ω)
B	0.03% (1kHz, 50 W, 8Ω)
Rear 20 watts per channel minimum RMS, both channels	Frequency response
driven, at 8 Ω 1 kHz with no more than 0.9% total	LINE (CD, TAPE, VIDEO)
harmonic distortion.	20 Hz ~ 60 kHz, +0 dB, -3 dB
namone distortion.	PHONO "RIAA" response20 Hz ~ 20 kHz, ± 0.5 dB
Total harmonic distortion	Maximum input level
0.06% (20 Hz ~ 20 kHz, 50 W, 8 Ω)	PHONO (MM) 120 mV, 0.5% T.H.D. at 1 kHz
0.03% (1kHz, 50 W, 8 Ω)	Signal to noise ratio
Frequency response	(IHF'66)
LINE (CD, TAPE, VIDEO)	PHONO (MM)75 dB
20 Hz ~ 60 kHz, +0 dB, -3 dB PHONO "RIAA" response	LINE (CD, TAPE, VIDEO)95 dB
20 Hz ~ 20 kHz, ± 0.5 dB	Input sensitivity/impedance
Maximum input level	PHONO (MM)3.5 mV/47 kΩ
PHONO (MM) 120 mV, 0.5% T.H.D. at 1 kHz	LINE (CD, TAPE, VIDEO)200 mV/47 kC2
Signal to noise ratio	ADAPTOR IN
(IHF'66)	Tone control BASS± 10 dB (at 100 Hz)
PHONO (MM)75 dB	TREBLE ± 10 dB (at 100 Hz)
LINE (CD, TAPE, VIDEO)95 dB	Loudness control (volume at -30 dB level)
Input sensitivity/impedance	+ 8 dB (100 Hz)
PHONO (MM)	Output level/impedance
LINE (CD, TAPE, VIDEO)200 mV/47 kΩ	TAPE REC
ADAPTOR IN200 mV/47 kΩ Tone control	ADAPTOR OUT200 mV/1 kg 2
BASS± 10 dB (at 100 Hz)	OCHERAL
TREBLE ± 10 dB (at 10 kHz)	GENERAL
Loudness control (volume at -30 dB level)	Power consumption250W
+ 8 dB (100 Hz)	AC outlet
Output level/impedance	SWITCHED300 W mix .
TAPE REC	Dimensions
ADAPTOR OUT200 mV/1 kΩ	H: 143 mm
GENERAL	D: 300 mm
GENERAL	Weight (Net)9.3 tg
Power consumption2.5 A	
250 W	
AC outlets	
SWITCHED2 (400 W max.)	
Dimensions	
H:143 mm (5-5/8")	
D: 300 mm (11-13/16")	

Note:

KENWOOD follows a policy of continuous advancements in development. For this reason specifications may be change; without notice.



SPECIFICATIONS

(KA-V3700)

AUDIO section

Rated power output	
STEREO MODE	
(DIN) 1 kHz	100 18/ - 100 18/
at 8 Ωat 4 Ω	W 00 + W 00
at 4 52	
SURROUND MODE	
(IHF 66) 1 kHz. 0.9 % T.H.D.at	B O.
FRONT	
CENTER	70 W
REAR	
Total harmonic distortion	
0.06% (
	0.03% (1 kHz, 50 W, 8 Ω)
Frequency response	
LINE (CD, TAPE, VIDEO)	
20	HZ ~ 55 KHZ, + U GB, -3 GB
PHONO "RIAA" response	2U HZ ~ 2 UKHZ, ± 0.5 @B
Maximum input level PHONO (MM)12	0 mV 0 5% T H D at 1 kHz
Signal to noise ratio	U III V, U.5 /6 1,11,D, at 1 KHZ
(DIN)	
PHONO(MM)	55 dB (50 mW output)
LINE (CD, TAPE, VIDEO)	57 dB (50 mW output)
Input sensitivity/impedance	-
PHONO (MM)	3.5 mV/47 kΩ
LINE (CD, TAPE, VIDEO)	200 mV/47 kΩ
ADAPTOR IN	200 mV/47 k Ω
Tone control	
BASS	
TREBLE	
Loudness control (volume at-	
O-4	+ 8 aB (100 Hz)
Output level/impedance TAPE REC	200 mV/1 kO
ADAPTOR OUT	200 mV/1 kO
ADAPTON OUT	
VIDEO section	
Input level/impedance	
VIDEO (composite)	1 Vp-p/75 Ω
Input (VIDÉO 1, VIDEO 2)	
Output level/impedance	
Output level/impedance VIDEO (composite)	1 Vp-p/75 Ω
Output (VIDEO 1, MONITOR	OUT)
07117011	
GENERAL	
Power consumption	220 141
AC outlets	320 VV
SWITCHED	(300 W max.)
Dimensions	W: 440 mm
	H: 143 mm
	D: 300 mm
Weight (Net)	9.3 kg
•	_

Note: KENWOOD follows a policy of continuous advancements in development. For this reason specifications m_{a_i} bechanged without notice.